

## PRODUCT INFORMATION

### Dimensions

Mini - L40 x W35 x H10mm  
Midi - L70 x W40 x H18.5mm  
Maxi - L75 x W38 x H18mm

### Weight

Mini - 12.5gram  
Midi - 20.0gram  
Maxi - 35.0gram

### Material specification

Produced in Sweden – from glass-fibre reinforced Nylon 6.  
Holdon™ in white contains UV stabilizers. Holdon™ in colours other than white are protected from UV deterioration by pigment additives, causing UV blocking with the highest protection in black.

### Standard colours available

Mini - white, green, blue, black, green, red, yellow.  
Midi - white, black, blue.  
Maxi - as for Mini Holdon™.

### Temperature range

Minus 30 degrees Celcius to +100 degrees Celcius. Melting temperature +220 degrees Celcius

### Median loading capacity

Mini - 70 kgs  
Midi - 100 kgs  
Maxi - 110 kgs

### Median loading - explanation

Median loading capacity is determined by a series of separate static loadings applied to a single Holdon™ installed on a 680/700 gms/sq.mtr. vinyl fabric (without hem). The median loading capacity represents the approximate safe working load that can be applied to the Holdon™, and in general terms determines the safe load bearing capacity of the bridge within the sleeve component.

**IMPORTANT** – the median loading capacity does not represent the efficiency or holding/gripping power or efficiency of the Holdon™ - those elements of performance are determined by both the correct application of the Holdon™ and by the physical characteristics of the fabric/substrate onto which the Holdon™ is being applied.

### Safety

The manufacturers and/or its distributors/agents make no claim whatsoever as to the holding/gripping efficiency or suitability of the Holdon™ clip and that the use of the product is the sole responsibility of the user(s).